

Wall-mounted air conditioners

NOVELTY!

SMART EASY PRO

It would be HOME



The latest SMART design solutions and advanced functions create a model with the greatest technological capabilities of the entire range of HYUNDAI air conditioners. Thanks to the "Intelligent Eye" function, the operation of the air conditioner saves even more energy.

Quiet operation, air ionization and advanced filters ensure health and comfort of use in your home home or office.

60% faster installation and maintenance



Energy-saving, class A+++



"INTELLIGENT EYE" function



Device features:

- | | | | | | | | | | |
|-------------------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------------------|----------------------------|-----------------------|--------------------|----------------------------------|
| Control WiFi | Auto restart | Auto cleaning | Intelligent defrosting | Function „Follow Me“ | Start with low power consumption | Standby mode 1W | Timer function | Weekly programming | +8°C maintaining temperature. |
| Mode | Engine DC | High density filters | Carbon Filter Active | Filter Catalytic | Ion filter Srebra | 12 fan speeds | Compatible with MULTI | A+++ Energy class | Double-sided condensate drainage |
| Connecting additional modules | SMART quick installation | Mode QUIET | Quiet operation 20dB(A) | 3D air supply air | Ionization Air | Function „Intelligent eye“ | Heater set Arctic Kit | | |

Technical data:

Set model	internal unit external unit	HRP-M09SEPI HRP-M09SEPO	HRP-M12SEPI HRP-M12SEPO	HRP-M18SEPI HRP-M18SEPO	HRP-M24SEPI HRP-M24SEPO
(kW) Nominal capacity		2.6	3.6	5.3	7.0
(W) Performance (range)	Cooling Warming	2725 (1318-3809) 3135 (879-4396)	3516 (1318-3956) 3956 (879-4542)	5275 (3751-6125) 5568 (2579-6769)	7033 (2110-8205) 7326 (1553-8205)
(W) Power consumption (range)	Cooling Warming	600 (130-1200) 690 (120-1400)	880 (130-1250) 990 (120-1450)	1318 (587-1787) 1500 (943-1695)	1760 (420-3200) 1975 (300-3100)
(A) Current consumption	Cooling Warming	2.66 (0.6-5.35) 3.05 (0.6-6.2)	3.9 (0.6-5.55) 4.4 (0.6-6.4)	5.73 (2.81-7.9) 6.52 (4.26-7.5)	7.7 (1.8-13.9) 10.2 (1.3-13.5)
(°C) Operating temperature range.	Cooling Warming	-25-50 -30-24	-25-50 -30-24	-25-50 -30-24	-25-50 -30-24
SEER/Energy Rating SCOP/Energy class	Cooling Warming	8.6/A+++ 4.6/A++	8.5/A+++ 4.6/A++	8.5/A+++ 4.3/A+	8.5/A+++ 4.2/A+
Unit inside	(m ³ /h) Air flow (H/M/L) (mm) Dimensions (L*W*D) (kg) Net weight (dB (A)) Sound pressure level (H/M/L/Q)	530/360/280 795x295x225 10.2 37/32/21.5/20.5	560/380/290 795x295x225 10.2 40/33/22/21	685/580/400 965x319x239 12.3 41/35/23/22	1092/724/379 1140x275x370 20.0 44.5/40/33/21
Unit outside	(mm) Dimensions (L*H*D) (kg) Net weight (dB (A)) Max. sound pressure level (dB (A)) Pressure level acoustic in night mode Factor type/quantity	805x554x330 28.4 57 44 R32/690	805x554x330 28.4 57.5 44 R32/690	890x673x342 38.8 56 45 R32/1100	890x673x342 45.6 58.5 46 R32/1500
Connection Installation	(inch) Liquid/gas pipe diameters (m) Maximum installation length/elevation	1/4"- 3/8" 25/10	1/4"- 3/8" 25/10	1/4"- 1/2" 30/20	3/8"- 5/8" 50/25
Connection Electric	(V/f/Hz) Voltage/number of phases/frequency (mm ²) Power cable to outdoor unit (<i>number of lines x cross-section</i>) (mm ²) Connection between units (<i>number of lines x cross-section</i>)	220-240/1/50 3x1.5 5x1.5	220-240/1/50 3x1.5 5x1.5	220-240/1/50 3x1.5 5x1.5	220-240/1/50 3x2.5 5x1.5

Accessories:

Standard		Optional			
					
PILOT	WiFi module	Wall controller	Controller with a weekly programmer	Controller group	Multifunctional module

Air conditioning equipment contains fluorinated greenhouse gases R32.

Due to continuous product improvement, specifications may change without notice.

Device photos are used for illustrative purposes only, the actual appearance may differ from the presented one.

Net prices in PLN included in the offer are catalog prices.